



# PVVM

# PVVM

Features	Caratteristiche	Merkmale	Caractéristiques
Connection by screwing together the two parts	Connessione avvitando maschio e femmina	Verbindung durch Verschrauben der beiden Teile	Connexion en dévissant les deux parties
Disconnection by unscrewing the two parts	Disconnessione svitando maschio e femmina	Entkuppeln durch Abschrauben	Déconnexion en dévissant les deux parties
Shut off by poppet valve	Sistema di tenuta mediante valvola a funghetto	Verschluß durch Kegelventil	Système d'étanchéité à clapet standard
Connectable under residual pressure	Innestabile con pressione residua	Kuppelbar unter Restdruck	Connectable sous pression résiduelle
Disconnection under residual pressure	Disconnessione con pressione residua	Entkuppelbar unter Restdruck	Déconnexion avec une pression résiduelle
Interchangeability German Market	Intercambiabilità mercato Tedesco	Austauschbarkeit deutschen Markt	Interchangeabilité marché Allemand


Fields of application  
Settori di applicazione  
Anwendungsbereiche  
Domaines d'application



Size Base BG Taille	Working pressure Pressione di esercizio Betriebsdruck Pression de service	Flow Rate Portata Durchsatz Débit	Burst Pressures Pressione di scoppio Berstdruck Pression d'éclatement
		@ 0,2 MPa pressure drop	



mm	inch.	MPa (PSI)	l/min (GPM)	MPa (PSI)	MPa (PSI)	MPa (PSI)
6.3	1/4"	103 (14935)	15 (3.96)	350 (50750)	310 (44950)	330 (47850)
10	3/8"	100 (14500)	20 (5.28)	350 (50750)	310 (47850)	300 (43500)

Technical Specifications	Specifiche Tecniche	Technischen Daten	Caractéristiques Techniques
High grade carbon steel with heat treated wear parts.	Acciaio ad alto tenore di carbonio con parti sollecitate, trattate termicamente	High Quality Karbonstahl Induktionsgärtet in besonders beanspruchter Stress zone	Acier à haute teneur en carbone avec traitement thermique des pièces d'usure
NBR Backup ring in PTFE	NBR Anello antiestrusione PTFE	NBR Stützring in PTFE	NBR Anneau anti-extrusion en PTFE
-25°C to +125°C (-13°F to +257°F)	-25°C a +125°C (-13°F a +257°F)	-25°C to +125°C (-13°F to +257°F)	-25°C à +125°C (-13°F à +257°F)
Mate500®	Mate500®	Mate500®	Mate500®
According to ISO 7241-2	Secondo la norma ISO 7241-2	Nach ISO 7241-2	Selon la norme ISO 7241-2



### Female - Femmina - Muffe - Femelle

Size Base BG Taille	Thread Filetto Anschluss Filetage	Part Number Codice Articolo Artikelnummer Désignation	A	B	D	L	P	X	Weight Peso Gewicht Poids	Package Confezione Verpackung Colis
mm	inch.		mm (in)	mm (in)	mm (in)	mm (in)	mm (in)	mm (in)	g (lbs)	No.
6.3	1/4"	F PVVM 1/14 NPT F	1/4" NPTF Male	63 (2.48)	30 (1.18)			21 (0.83)		
10	3/8"	F PVVM 1/38 NPT F	3/8" NPTF Male	84 (3.31)	36 (1.42)			25 (0.98)		



### Male - Maschio - Stecker - Male



Size Base BG Taille	Thread Filetto Anschluss Filetage	Part Number Codice Articolo Artikelnummer Désignation	E	C	H	L	Y	Weight Peso Gewicht Poids	Package Confezione Verpackung Colis
mm	inch.		mm (in)	mm (in)	mm (in)	mm (in)	mm (in)	g (lbs)	No.
6.3	1/4"	M PVVM 14 NPT M	1/4" NPTF Female	34 (1.34)	15.8 (0.62)	B+C-19 (0.75)	27 (1.06)		
10	3/8"	M PVVM 38 NPT M	3/8" NPTF Female	39 (1.54)	19 (0.75)	B+C-25 (0.98)	27 (1.26)		

### Accessories - Accessori - Zubehör - Accessoires

Size Base BG Taille	Dust protections Tagli Protezione Staubschutzteile Capuchons	Dust protections Tagli Protezione Staubschutzteile Capuchons	Seal Kits Guarnizioni di ricambio Ersatzdichtungen Joints	Package Confezione Verpackung Colis
mm	inch	Part Number Codice Articolo Artikelnummer Désignation	Part Number Codice Articolo Artikelnummer Désignation	
6.3	1/4"	TFP 14	TMP 14	SK PVVM 14 1*
10	3/8"	TFP 38	TMP 38	SK PVVM 38 1*

\*10 O-rings + 10 PTFE rings

### Thread Filetto Anschluss Filetage



ISO A - ISO B - Standard  
ISO A - ISO B - Standard  
ISO V - ISO B - Standard  
ISO V - ISO B - Standard

Agriculture  
Agriculture  
Ausführung Agrichtechnik  
Agriculture

Screw Together  
Screw Together  
Schräbklüpfungen  
A Visser

Check Valves  
Valvoni  
Rückschluventile  
Clapet Anti-retour

Diagnostic  
Diagnostik  
Diagnostik  
Diagnostik

Flat Face  
Innessi Face piana  
Flächendichtend  
Clapet a Face Plate

Multi-seal  
Multi-seal  
Multi-sealungen  
Multi-seal